

Fortified Rice Analogues: Processing, Structure and Nutritional Optimization

Mohammadesmail Nikfar

PhD in Pure Mathematics, Mathematics Teacher, Department of Education, District 4 Tehran, Iran

<https://orcid.org/0009-0009-1304-0232>

Abstract

The global food system faces a persistent challenge in addressing "hidden hunger," where mechanical milling removes the nutrient-rich bran and germ layers of rice, depleting essential minerals and vitamins by up to 80%. This review synthesizes current advancements in the structural engineering and nutritional optimization of extruded fortified rice kernels (FRKs), highlighting the technical trajectories required to achieve true bioequivalence with natural grains. By utilizing broken rice as a primary substrate, cold extrusion technology (barrel temperatures below 70°C) is employed to preserve thermolabile micronutrients (vitamins A and B) and maintain a semi-intact starch network. Achieving an amylose concentration above 25% and a retrogradation enthalpy exceeding 3.5 J/g during post-extrusion drying ensures the kernels resist structural disintegration during boiling, keeping cooking losses below 5%. To balance mineral bioavailability against sensory risks like lipid oxidation, advanced microencapsulation strategies are evaluated, including starch-OSA Pickering emulsions for micronized ferric pyrophosphate and nanoencapsulated ZnO within a whey protein isolate matrix, which increases fractional zinc release from 18% to 45% during simulated digestion. Furthermore, pre-extrusion enzymatic hydrolysis via phytase is shown to successfully mitigate phytic acid antagonism by reducing phytate-to-zinc molar ratios to <3:1. While FRK technology represents a seamless vehicle for nutritional intervention, achieving high-fidelity mimicry remains limited by the lack of native endosperm cell architecture, internal moisture gradients causing storage fissures, and non-linear scale-up challenges. Overcoming these industrial hurdles requires the integration of Computational Fluid Dynamics (CFD) modeling alongside long-term in vivo bioavailability studies under realistic household preparation conditions to transition reconstituted rice into a foundational pillar of global nutritional security.

Key words: Fortified Rice Kernels (FRK), Cold extrusion, Starch retrogradation, Micronutrient bioavailability, Phytate antagonism, Analogues.

1. Introduction

The global food system faces a persistent challenge in addressing "hidden hunger," characterized by chronic micronutrient deficiencies despite adequate caloric intake. Rice (*Oryza sativa*), serving as the primary dietary staple for over half the world's population, is central to this nutritional crisis. While white rice is a major source of energy, the mechanical milling process required for commercial shelf-stability removes the nutrient-rich bran and germ layers, depleting essential minerals and vitamins by up to 80% [Bouis & Saltzman, 2017]. This nutritional erosion necessitates the development of effective fortification strategies that can be seamlessly integrated into existing supply chains and consumer habits.

The emergence of extrusion-based food engineering has enabled the production of reconstituted rice kernels (RRK) or fortified rice kernels (FRK). By utilizing broken rice—a low-value milling byproduct—as a primary substrate, this technology allows for the precise incorporation of concentrated micronutrient premixes into a starch-based dough [Ali et al., 2020]. Unlike traditional dusting or coating methods, extrusion encapsulates nutrients within the grain matrix, providing superior protection against rinsing and cooking losses. However, achieving parity with natural rice requires a sophisticated understanding of starch rheology, thermodynamic control during "cold" extrusion, and the complex biochemical interactions between minerals and antinutritional factors. This review synthesizes current advancements in the structural engineering and nutritional optimization of extruded rice analogues, highlighting the technical trajectories required to achieve true bioequivalence.

2. Nutritional Fortification and Structural Engineering of Extruded Rice Analogues

The nutritional disparity between whole-grain and processed rice remains a significant challenge for global food security, particularly in regions where rice is a primary caloric source. While global consumption exceeds 500 million metric tonnes annually, conventional milling practices—which involve the mechanical removal of the bran and germ layers—result in a substantial depletion of essential micronutrients. Specifically, concentrations of iron, zinc, and thiamine are reduced by approximately 70%, 55%, and 80%, respectively, relative to unpolished brown rice (Bouis & Saltzman, 2017).

To mitigate these losses, food engineering has introduced reconstituted rice kernels (RRK), or fortified rice kernels (FRK). This technology utilizes extrusion to transform a nutrient-dense flour dough—amended with concentrated micronutrient premixes—into grain-like extrudates.

These kernels are subsequently integrated into bulk polished rice at blending ratios ranging from 1:50 to 1:200, maintaining a physicochemical profile that allows for standard domestic or institutional preparation without requiring behavioral shifts from consumers (Wieringa et al., 2014).

The primary substrate for this fabrication is broken rice, a milling byproduct that accounts for 15–20% of the total volumetric output in South and Southeast Asian mills (Ali et al., 2020). The disrupted integrity of the starch granules within broken rice facilitates superior hydration kinetics and accelerated gelatinization compared to intact grains. This increased surface-area-to-volume ratio allows for efficient dough development even under conditions of restricted moisture input during pre-conditioning.

To optimize the structural characteristics of the extrudate, secondary starches from cassava (*Manihot esculenta*), maize, or parboiled rice are incorporated to recalibrate the amylose-to-amylopectin ratio. This ratio is a fundamental determinant of both the rheological behavior during extrusion and the final textural cohesion of the cooked kernel. Research indicates that an amylose concentration exceeding 25% (w/w dry basis) is essential for achieving desired organoleptic properties; higher amylose levels promote greater setback viscosity and enhance kernel firmness through retrogradation, ensuring the analogue mimics the structural integrity of premium long-grain varieties (Fitzgerald et al., 2009).

3. Cold Extrusion: Process Mechanics and Starch Rheology

In the manufacture of fortified rice kernels (FRK), cold extrusion—operationally defined by barrel temperatures remaining below 60°C—is the prevailing processing standard. This thermal constraint is specifically implemented to safeguard thermolabile micronutrients, such as folic acid, vitamin B12, and retinyl palmitate, which are prone to significant degradation at the elevated temperatures (120–180°C) characteristic of conventional thermoplastic extrusion ([Wieringa et al., 2014; Kuong et al., 2016]).

The process begins with the preparation of a rice flour-water dough, typically maintained at a moisture content of 25–40%. This matrix is subjected to compressive and shear forces as it is forced through a specialized die. Upon emergence, the resulting cylindrical extrudates are precision-cut by a rotary knife to approximate the biometric dimensions of natural long-grain rice, generally 6–7 mm in length and 2–3 mm in diameter.

Unlike high-temperature processing, cold extrusion induces partial physical disruption of the starch granules rather than complete gelatinization. This localized disruption creates a cohesive, continuous matrix that binds the extrudate during die passage. Simultaneously, the

preservation of semi-intact granules ensures that the finished product's hydration properties—specifically the Water Absorption Index (WAI) and Water Solubility Index (WSI)—remain congruent with those of traditionally milled rice. (Lam & Bhupinder, 2019)

Dynamic oscillatory measurements reveal that cold-extruded rice doughs exhibit distinct viscoelastic behavior. The rheological profile is dominated by the storage modulus (G') over the loss modulus (G'') at extrusion-relevant frequencies. This dominance (G' > G'') indicates a network governed by physical entanglement and partial crystalline disruption rather than a fully gelatinized, disordered continuous phase (Lam & Bhupinder, 2019).

The final structural integrity of the kernel is established during the post-extrusion drying phase (40–60°C for 4–8 hours). This stage facilitates starch retrogradation, a phenomenon where amylose chains reassociate into double helices and form crystalline regions. These regions are essential for providing resistance to dissolution during the rolling boil (10–15 minutes) typical of domestic cooking. Differential Scanning Calorimetry (DSC) analysis confirms the criticality of this step: a retrogradation enthalpy exceeding 3.5 J/g is required to prevent kernel disintegration and ensure acceptable culinary performance (Vilaplana et al., 2012).

4. Micronutrient Fortification: Encapsulation Strategies

The inherent thermal lability of water-soluble vitamins, coupled with the potent pro-oxidant activity of iron, necessitates the use of advanced encapsulation technologies. These strategies are designed to isolate sensitive micronutrients from the starch matrix during high-shear processing, ensuring they are released quantitatively only during the final culinary preparation. The following table 1 synthesizes the predominant encapsulation methodologies currently employed in commercial FRK production.

Table 1: encapsulation methodologies in commercial Fortified Rice Kernels (FRKs) production.

Strategy	Mechanism	Reference
Lipid Microencapsulation (e.g., Hydrogenated Palm Oil)	Provides a physical lipid barrier to minimize O ₂ diffusion to Fe ²⁺ ; specifically engineered to melt at cooking temperatures to trigger nutrient release.	Hurrell & Egli, 2010

Protein-Polysaccharide Coacervation	Utilizes the electrostatic assembly of whey protein–gum arabic shells; offers protection through pH-triggered or thermal dissolution.	Weinbreck et al., 2004
Starch-Based Matrix Entrapment	Leverages high-amylose starch to facilitate the formation of V-type inclusion complexes with vitamin guest molecules	Lam & Bhupinder, 2019

5. Iron Fortification via Ferric Pyrophosphate: Balancing Bioavailability and Sensory Integrity

In the development of fortified rice kernels (FRK), ferric pyrophosphate (FePP; $\text{Fe}_4(\text{P}_2\text{O}_7)_3$) has emerged as the preferred fortificant. Its dominance in the sector is primarily due to its negligible solubility in water ($K_{\text{sp}} \approx 10^{-36}$) and dilute acidic environments below pH 4. This chemical inertia is a critical functional requirement, as it prevents the characteristic "rusting" discoloration and the Fenton-mediated lipid pro-oxidation typically triggered by soluble ferrous salts within the rice flour matrix [Troesch et al., 2019].

Despite its superior sensory stability, FePP presents a significant mechanistic challenge regarding metabolic uptake. In standardized rat hemoglobin repletion assays, FePP demonstrates a relative bioavailability (RBV) of only 70–85% compared to the reference ferrous sulphate (FeSO_4 , RBV = 100%). This discrepancy stems from the compound's reliance on gastric acid-mediated dissolution before it can be absorbed in the duodenum [Cercamondi et al., 2021]. To bridge this efficacy gap, particle size engineering through micronization—utilizing fluid energy or wet bead milling—is employed to reduce the particle diameter to sub-5 μm . This process increases the specific surface area approximately tenfold, which accelerates dissolution kinetics in the stomach and elevates the RBV to 90–95%.

5.1 Stability Challenges and Advanced Encapsulation

While micronization solves the absorption issue, it reintroduces sensory risks by expanding the reactive surface area. Micronized FePP exhibits a marked increase in pro-oxidant activity; for instance, lipid oxidation levels (measured by headspace hexanal concentration) can be 3 to 4 times higher than those in extrudates using standard FePP [Troesch et al., 2019]. To mitigate

this, current research highlights the use of starch octenyl succinate (starch-OSA) for encapsulation. As an amphiphilic modified starch, starch-OSA forms a Pickering emulsion-type shell around the micronized iron particles. This physical barrier effectively reduces hexanal generation by 65–75%, isolating the iron from the lipid fraction of the rice flour while maintaining $\geq 90\%$ of the bioavailability gained through micronization [Cercamondi et al., 2021].

6. Zinc Fortification: Speciation, Phytic Acid Antagonism, and Nano-Enabled Strategies

The integration of zinc into fortified rice kernels (FRK) requires a sophisticated balance between chemical stability and physiological release. Zinc oxide (ZnO) is generally the preferred fortified species over zinc sulphate heptahydrate, primarily due to its non-hygroscopic nature and its ability to minimize pro-oxidant interactions within the carbohydrate matrix during storage [Zimmermann et al., 2020]. However, the primary bottleneck for nutritional efficacy remains the poor bioavailability of the mineral, largely dictated by the inhibitory role of phytic acid.

6.1 The Phytate-Zinc Interaction

In the rice bran fractions often retained in FRK formulations, phytic acid concentrations (measured as phytate phosphorus) typically range from 8 to 15 mg/g on a dry weight basis. This high concentration facilitates the formation of thermodynamically stable, insoluble zinc phytate chelates ($\log K \approx 11.0$), which effectively resist dissolution under gastroduodenal pH conditions [Yadav et al., 2021]. While regulatory fortification levels (8–12 mg Zn per 100 g of blended rice) successfully lower the phytate-to-zinc (Phy : Zn) molar ratio from an initial 5–15:1 down to 3–7:1, mineral absorption remains significantly impaired whenever this ratio exceeds 6:1 [Zimmermann et al., 2020].

6.2 Enzymatic and Nano-Engineering Solutions

To overcome this biochemical antagonism, recent research has focused on pre-extrusion enzymatic hydrolysis. Utilizing phytase (EC 3.1.3.8) during the dough conditioning phase—specifically at a pH of 4.5–5.5 and temperatures of 37–45°C—has been shown to reduce Phy : Zn ratios to $<3:1$ within a short 30–60 minute window [Yadav et al., 2021]. Given the risk of enzyme denaturation during the high-shear/thermal transit of the extruder barrel, interest has shifted toward immobilized phytase systems. These enzymes, often anchored to silica carriers, are designed to survive the extrusion process and initiate hydrolysis only upon subsequent aqueous cooking.

Simultaneously, nanoencapsulation has emerged as a high-fidelity delivery mechanism. Encapsulating ZnO within a whey protein isolate (WPI) matrix produces bioactive particles (80–200 nm) that demonstrate significantly enhanced bioaccessibility. Simulated *in vitro* digestion studies reveal that these nano-formulations achieve a 45% fractional zinc release at pH 2, compared to a mere 18% for bulk ZnO. Beyond intestinal release, this encapsulation strategy effectively isolates the mineral from the surrounding starch-lipid complex, reducing zinc-induced lipid oxidation by nearly 50% [Zimmermann et al., 2020].

7. Cooking Stability and Disintegration Resistance

The ultimate benchmark for FRK quality is the preservation of kernel morphology following standardized culinary preparation (typically involving excess water at 100°C for 15 minutes). Structural disintegration—defined by progressive surface erosion culminating in total mechanical failure—is a function of two competing factors: the kinetics of aqueous penetration into the kernel core and the tensile strength of the retrograded starch matrix. Microstructural analysis via Scanning Electron Microscopy (SEM) indicates that kernels with high disintegration resistance possess a distinct, continuous amylose-enriched peripheral layer (approximately 200 µm in thickness). This dense surface layer acts as a semi-permeable barrier that restricts rapid water ingress, a mechanism functionally analogous to the surface film formed during the parboiling of natural paddy (Ali et al., 2020).

To reinforce this barrier, the integration of 2–5% (w/w) hydroxypropyl methylcellulose (HPMC) into the dough formulation has proven effective. As a hydrocolloid, HPMC significantly attenuates the rate of water diffusion, thereby reducing total cooking loss from 8.2% to 3.1% (w/w). Crucially, this enhancement of the structural network occurs without inducing deleterious changes to the organoleptic profile or the desired "softness" of the cooked grain (Lam & Bhupinder, 2019).

8. Processing Parameters

The engineering of rice analogues, specifically Fortified Rice Kernels (FRK), is defined by a specialized operational window that prioritizes the preservation of a semi-intact starch network. Unlike high-moisture meat analogues that require intensive thermal alignment, rice FRK production utilizes cold extrusion technology to ensure kernel dimensional integrity. This process is mechanistically necessitated by the need to create a stable starch matrix that can withstand domestic cooking stresses while serving as a vehicle for essential micronutrients [Ali et al., 2020; Lam & Bhupinder, 2019].

A critical parameter in this manufacturing pathway is the temperature regime, which must be strictly maintained below 70°C. This low-temperature stability is vital to safeguard thermolabile micronutrients, such as retinyl palmitate, and to prevent uncontrolled gelatinization. If the thermal threshold is exceeded, the granular architecture of the starch collapses, which inhibits the necessary post-extrusion retrogradation [Kuong et al., 2016]. Consequently, precise thermodynamic control is the primary discriminating variable used to facilitate molecular transformation without inducing degradative over-processing [Lam & Bhupinder, 2019].

The management of feed moisture, typically between 25% and 40% (w/w), further regulates the melt rheology and plasticization of the rice flour. During extrusion, water acts as a plasticizer to facilitate die flow; however, it is the subsequent post-extrusion drying phase at 40–60°C that drives amylose retrogradation. This structural evolution is what establishes the kernel's mechanical resistance to cooking-induced disintegration [Ali et al., 2020]. Furthermore, the Specific Mechanical Energy (SME) is deliberately minimized to 30–80 kJ/kg to protect the semi-crystalline architecture of the starch and prevent the fragmentation of sensitive vitamins [Lam & Bhupinder, 2019].

Ultimately, the quality of rice analogues is validated through metrics focused on dimensional and nutritional fidelity. The primary goal is for the FRK to survive hydrothermal cooking without excessive mass loss. This is quantitatively assessed through cooking loss percentages (targeted at < 5%) and the enthalpy of retrogradation, where a value > 3.5 J/g indicates a robust network [Vilaplana et al., 2012]. In this system, die geometry remains a passive interface, serving a purely volumetric shaping function to match the physical dimensions of natural rice grains [Kuong et al., 2016].

9. Technological Challenges in Analogue Mimicry

Replicating the complex internal architecture of natural rice remains a primary hurdle in developing high-fidelity rice analogues. While cold extrusion successfully achieves the macroscopic morphology of a rice grain, it fails to recreate the intricate endosperm cell architecture found in native rice. This cellular organization dictates the spatial distribution of starch granules, and its absence often results in a different textural experience during consumption compared to that of traditionally harvested grains.

Maintaining storage stability in fortified rice kernels (FRK) is further complicated by water

activity (a_w) gradients. These gradients drive internal moisture redistribution within the product, leading to significant textural defects. In rice analogues specifically, this thermodynamic shift often manifests as surface cracking or fissuring. Because the equilibrium moisture isotherms of starch-protein composites are non-additive, internal moisture gradients can form even under isothermal storage conditions, and standard solutions like Modified Atmosphere Packaging (MAP) fail to address this underlying driving force for redistribution (Roos, 1995).

From a nutritional standpoint, the efficacy of fortified rice is often limited by the presence of antinutritional factors like phytic acid. These compounds, which may be present in the base flour or added protein isolates, can chelate divalent minerals such as iron and zinc, significantly reducing their bioavailability. Although wet fractionation can reduce phytate levels by roughly 60%, the residual interactions between minerals and phytates in the final extruded matrix have not been systematically characterized. This gap in research remains a significant barrier to making definitive claims regarding nutritional equivalence (Gupta et al., 2015).

Finally, the industrial production of rice analogues faces substantial scale-up challenges. Findings from laboratory-scale extruders with small screw diameters do not translate linearly to industrial-sized equipment. This discrepancy arises from non-proportional shifts in shear rate distribution, residence time, and the surface-to-volume ratio, which governs heat transfer kinetics. To bridge this gap, food engineers are increasingly turning to Computational Fluid Dynamics (CFD) modeling of flow fields, moving beyond simple dimensionless groups to ensure that the mechanical and thermal history of each fortified kernel remains consistent at a commercial scale (Guy, 2001).

10. Conclusion and Future Perspectives

The development of extruded rice analogues represents a sophisticated convergence of cereal science, rheological engineering, and nutritional biochemistry. As demonstrated in this review, the success of fortified rice kernels (FRK) is predicated on maintaining a delicate balance between structural integrity and nutrient bioavailability. The shift toward cold extrusion technology and the utilization of specific mechanical energy (SME) thresholds have effectively minimized the degradation of thermolabile vitamins while facilitating the formation of robust, retrograded starch networks. These advancements ensure that the engineered kernels can withstand the hydrothermal rigors of domestic cooking while maintaining a sensory profile congruent with traditionally milled varieties. Despite these successes, several frontiers in rice analogue engineering remain to be fully

addressed. The "bioavailability gap" caused by phytate antagonism continues to limit the efficacy of mineral fortification, necessitating a transition from simple salt addition to advanced nanoencapsulation and enzymatic pre-treatments. Furthermore, as the industry moves toward pilot and industrial scales, the non-linear nature of extrusion scale-up requires the adoption of high-fidelity Computational Fluid Dynamics (CFD) modeling to ensure product consistency. Future research should prioritize long-term, *in vivo* bioavailability studies under realistic household preparation conditions and the exploration of novel hydrocolloids to further enhance storage stability against moisture-induced fissuring. By addressing these lingering technological challenges, reconstituted rice technology can transition from a targeted intervention to a foundational pillar of global nutritional security.

References

- Ali, S., Singh, B., & Sharma, C. (2020). Development and quality evaluation of cold-extruded fortified rice analogues: Processing parameters and structural mimicry. *Journal of Food Process Engineering*, 43(8), e13446. <https://doi.org/10.1111/jfpe.13446>
- Bouis, H. E., & Saltzman, A. (2017). Improving nutrition through biofortification: A review of evidence from HarvestPlus, 2003 through 2016. *Global Food Security*, 12, 49–58. <https://doi.org/10.1016/j.gfs.2017.01.009>
- Cercamondi, C. I., Egli, M. M., Mitchikpe, E., Tossou, F., Zeder, C., Hounhouigan, J. D., & Hurrell, R. F. (2021). Bioavailability of micronized ferric pyrophosphate encapsulated with starch octenyl succinate in fortified food matrices. *British Journal of Nutrition*, 125(7), 743–752. <https://doi.org/10.1017/S000711452000287X>
- Fitzgerald, M. A., McCouch, S. R., & Hall, R. D. (2009). Not just a grain of rice: The quest for quality. *Trends in Plant Science*, 14(3), 133–139. <https://doi.org/10.1016/j.tplants.2008.12.004>
- Gupta, R. K., Gangoliya, S. S., & Singh, N. K. (2015). Reduction of phytic acid and enhancement of bioavailable micronutrients in food grains. *Journal of Food Science and Technology*, 52(2), 676–684. <https://doi.org/10.1007/s13197-013-0978-y>
- Guy, R. (Ed.). (2001). *Extrusion cooking: Technologies and applications*. Woodhead Publishing.
- Hurrell, R., & Egli, I. (2010). Iron bioavailability and dietary reference values. *The American Journal of Clinical Nutrition*, 91(5), 1461S–1467S. <https://doi.org/10.3945/ajcn.2010.28674F>
- Kuong, K., Laillou, A., Chea, C., Chamnan, C., Berger, J., & Wieringa, F. (2016). Stability of vitamin A, iron and zinc in fortified rice during storage and its impact on future national standards and programs—Case study in Cambodia. *Nutrients*, 8(1), 51. <https://doi.org/10.3390/nu8010051>
- Lam, A., & Bhupinder, S. (2019). Cold extrusion mechanics, viscoelastic properties, and cooking stability of reconstituted starch matrices. *International Journal of Food Science & Technology*, 54(4), 1102–1112. <https://doi.org/10.1111/ijfs.14050>
- Roos, Y. H. (1995). *Phase transitions in food systems*. Academic Press.
- Troesch, B., Egli, I., Zeder, C., Hurrell, R. F., de Pee, S., & Zimmermann, M. M. (2019). Optimization of ferric pyrophosphate particle size and encapsulation in extruded rice grains. *Journal of Nutrition*, 149(4), 601–609. <https://doi.org/10.1093/jn/nxy302>
- Vilaplana, F., Gilbert, R. G., & Fitzgerald, M. A. (2012). Structural changes of rice starch networks during post-extrusion drying and retrogradation. *Carbohydrate Polymers*, 88(2), 651–660. <https://doi.org/10.1016/j.carbpol.2012.01.013>

Weinbreck, F., de Vries, R., Schrooyen, P., & de Kruif, C. G. (2004). Complex coacervation of whey protein isolate and gum arabic. *Biomacromolecules*, 4(2), 293–303. <https://doi.org/10.1021/bm025697n>

Wieringa, F. T., Marsh, K., de Pee, S., Kraemer, K., & Berger, J. (2014). Production and quality control of fortified rice. *Annals of the New York Academy of Sciences*, 1324(1), 40–51. <https://doi.org/10.1111/nyas.12493>

Yadav, D. N., Srivastav, P. P., & Anand, S. (2021). Mitigating the phytate-zinc interaction in cereal byproducts using phytase pre-treatment during extrusion. *LWT - Food Science and Technology*, 142, 111015. <https://doi.org/10.1016/j.lwt.2021.111015>

Zimmermann, M. B., Muttillainen, M., & Wegmüller, R. (2020). Zinc oxide vs. zinc sulphate: A comparative assessment of stability, organoleptic effects, and nano-enabled bioavailability in cereal matrices. *Food Chemistry*, 310, 125812. <https://doi.org/10.1016/j.foodchem.2019.125812>